



12	1/2000		25P D-SUB G/F FEMALE PLASTIC BLACK	测试头	
11	1/2000		8P8C 水晶头 G/F PLUG	测试头	
10	1		LABEL: L?*W?mm 印字内容: "POWER HARNESS POWER-NR0001"	MEET ROHS & LEAD FREE	
9	0.2g	AN00000227	无铅锡丝: $\phi 1.0\text{mm}$	MEET ROHS & LEAD FREE	
8	7g		PE	MEET ROHS & LEAD FREE	
7	20g		PVC: BLACK SHOREA 87 \pm 3(45P)	MEET ROHS & LEAD FREE	
6	2		TER	MEET ROHS & LEAD FREE	
5	2		4-40# UNC-2A THUMB SCREW BLACK	MEET ROHS & LEAD FREE	
4	1		25P D-SUB G/F FEMALE PLASTIC BLACK	MEET ROHS & LEAD FREE	
3	1		水晶头 G/F PLUG	MEET ROHS & LEAD FREE	
2	1	8P8C	CABLE: 2x0.75mm ² BLACK L=1890mm OD3.2*6.4mm	MEET ROHS & LEAD FREE	
1	1		CABLE: CAT.5E UTP #24x4PAIRS BLACK(GTL-005) OD=5.5mm L=1890mm	MEET ROHS & LEAD FREE	
ITEM	Q'TY	P/N	DESCRIPTION		VENDOR

ELECTRONIC TEST:
 1.VOLTAGE: DC 300V/5M/10ms
 2.CONTACT RESISTANCE: 5.0ohm(MAX)
 3.100% OPEN & SHORT.

WIRING TABLE

P1	COLOR	P2	COLOR	P3
3	WHITE/GREEN	2		
4	BLUE	6		
5	WHITE/BLUE	20		
6	GREEN	7		
7	WHITE/BROWN	4	GRAY	+
8	BROWN	5	BLACK	-

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

DRAWING BY CY

X, \pm

CHECKED BY GENIUS

.X \pm

UNIT / mm

SCALE 1 : 1

.XXX \pm

DATE

ANG \pm

照片框

ORDER INFORMATION

DBX12-252824C5E-A6F-LF

SERIES

LEADFREE
 1830mm
 FEMALE TO MALE

CAT.5E
 24 AWG
 25/2/8 PIN

煜倫股份有限公司

www.morethanall.com

SIZE A4

PPOJECTION

DESCRIPTION: