



***CONSTRUCTION:

1.CABLE: * UL2464 9C/26AWG+EA OD:6.0mm GRAY JACKET.

***CONNECTORS:

2.DB9: * D-SUB 9PIN MALE & FEMALE SOLDER TYPE.
 * PINS: BRASS WITH GOLD PLATED.
 * SHELL: STEEL WITH NICKEL PLATED.
 * INSULATOR: WHITE COLOR P.B.T UL 94V-0 RATED.
 * SCREW: THUMSCREW #4-40 UNC GRAY COLOR.
 * SHIELD: SHIELD BY METAL HOOD.
 * HOOD: GRAY PVC.

4.TEST: * CT: 2 ohm IS: 5M ohm.

5.PACKING: * PACK EACH CABLE IN A POLY BAG.

6.MATERIAL: * MATERIAL WITH RoHS GRADE.

PIN OUT

DB 9M	DB 9F
1	1
2	2
3	3
4	4
5	5
6	6
7	7
8	8
9	9
SHELL	DRAIN
	SHELL

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

RoHS Compliant

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

TOLERANCES ARE

X.±

.X±

.XX±

.XXX±

ANG±

PPOJECTION

照片框

ORDER INFORMATION

DBX2-090926-E1M8-LF

SERIES

LEADFREE

1800mm

MALE TO FEMALE

26 AWG

09 TO 09 WAY

DESCRIPTION: D-SUB 9PIN MALE TO FEMALE