



NO	ITEM	Q' TY	DESCRIPTION
1	CABLE	1pcs	UL2464 #28 *9C(BLACK, BRWON, RED, ORANGE, YELLOW, GREEN, BLUE, PURPLE, WHITE)+AEB JACKET:BLACK OD:5.8
2	CONN	1pcs	DB25M MALE SOLDER BLACK INSULATION
3	INMOLDED	12.4g	PE NO: GH-221
4	OUTMOLDED	47g	PVC 45P BLACK NO: GH-222
5	SCREW	2pcs	LARGE E321 #4-40UNC BLACK
6	CONN	1pcs	DB15M MALE SOLDER BLACK INSULATION
7	INMOLDED	5.5G	PE NO:GH-158
8	OUTMOLDED	15.6G	PVC 45P BLACK NO: GH-159
9	SCREW	2pcs	LARGE E23 #4-40UNC BLACK

A	COLOR	B
13	BLACK	3
14	BRWON	10
10	RED	2
9	ORANGE	9
12	YELLOW	4
11	GREEN	11
19	BLUE	6
21	PURPLE	13

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT/mm SCALE 1:1

DATE

SIZE A4

X.±  
.X±  
.XX±  
.XXX±  
ANG±

PJECTION

照片框

ORDER INFORMATION

DBX2-152528-M4F-LF

SERIES | | | LEADFREE  
| | | 1220mm  
| | | MALE TO MALE  
| | | 28 AWG  
| | | 15 TO 25 WAY

DESCRIPTION: