

DGC 25 M/F GENDER CHANGER

PIN OUT: 25Male 25Female

1	-----	1
2	-----	2
}		
24	-----	24
25	-----	25
G	-----	G

Label: yellow color with black character
One side: MINI GENDER CHANGER

The other side: U.S.A. PATENT 5199906

SPECIFICATION

INSULATOR: PBT Glass fibre reinforced UL 94 V0

CONTACT: Brass

CONTACT PLATING: Gold plated over nickel

SHELL: Tin plated shell

CURRENT RATING: 3 AMP

DIELECTRIC STRENGTH: 1000V AC for one minute

INSULATOR RESISTANCE: 1000MΩ min at 500V DC

TEMPERATURE: -55°C — +105°C

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

X.±

CHECKED BY GENIUS

.X±

UNIT / mm

SCALE 1 : 1

.XX±


DATE

.XXX±

SIZE A4

PPOJECTION

ANG±



ORDER INFORMATION

DBX2-ES-2525-LF

SERIES | LEADFREE

25 TO 25 WAY

MALE TO FEMALE

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: