



RECOMMENDED P.C.B. LAYOUT

SPECIFICATIONS

ELECTRICAL CHARACTERISTICS:

Contact Current Rating:3 Amperes.
 Dielectric Withstanding Voltage: AC 1000/60sec.r.m.s.
 Insulation Resistance:500 Medohms Minimum.at DC 500V.
 Contact Resistaance:25 Milliohms Maximum.
 Operating Temperature:-55°C to+105°C.

MECHANICAL CHARACTERISTICS:

Contact Insertion Force:341 g.Maximum.
 Contact Separation Force:21 g.Minimum.
 Grounding Screw Torque:3 Kg.Minimum.

MATERIALS:

Contacts:Brass.
 Insulator: PBT UL 94V-0 Rated.
 Shell:Cold Roller Steel.
 Grounding Screw Torque:Brass

FINISHES:

Contact:Gold Flash.
 Shell:Nickel Plated.

DCD-PSZ-09-LF
 LEADFREE

RoHS Compliant



PART NO. DCD-PSZ-09

DWG NO. DCD-PSZ-09

FILE NO.

CHECKED BY CY

DRAWING BY

TOLERANCES ARE
 .X ± 0.2
 .XX ±
 .XXX ±
 AWG

DESCRIPTION:
 AREA

D-SUB CONNECTOR CRIMP TYPE			
REVISIONS	HK	DATE	

煜倫股份有限公司

UNIT / mm SCALE 1:1

PROJECTION