



RECOMMENDED P.C.B. LAYOUT

## SPECIFICATIONS

### ELECTRICAL CHARACTERISTICS:

Contact Current Rating: 3 Amperes.  
 Dielectric Withstanding Voltage: AC 1000/60sec.r.m.s.  
 Insulation Resistance: 500 Megohms Minimum at DC 500V.  
 Contact Resistance: 25 Milliohms Maximum.  
 Operating Temperature: -55°C to +105°C.

### MECHANICAL CHARACTERISTICS:

Contact Insertion Force: 341 g Maximum.  
 Contact Separation Force: 21 g Minimum.  
 Grounding Screw Torque: 3 Kg Minimum.

### MATERIALS:

Contacts: Brass.  
 Insulator: PBT UL 94V-0 Rated.  
 Shell: Cold Roller Steel.  
 Grounding Screw Torque: Brass

### FINISHES:

Contact: Gold Flash.  
 Shell: Nickel Plated.

DCD11-PSZJ-25-LF

LEADFREE

RoHS Compliant

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
 PCB CONNECTORS  
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

P PROJECTION

X. ±

.X ±

.XX ±

.XXX ±

ANG ±

照片框

ORDER INFORMATION

DCD106-PSZJ-25-LF

SERIES

LEADFREE

25 WAY

MALE CLIP

SEMI GOLD

DESCRIPTION: D-SUB CONNECTOR CRIMP TYPE