



RECOMMENDED P.C.B LAYOUT
INSPECTION DIMENSION:(A)~(G)

NOTES

1. MATERIAL:
Housing:PBT, UL 94V-0, Color:Black.
Terminal:Copper Alloy.
Shell:SPCC.
Boardlock:Copper Alloy.
2. FINISH:
Terminal:Gold Plated over Nickel at Contact Area.
Tin Plated over Nickel at Solder Area.
Shell:Tin Plated.
Boardlock:Tin Plated.
3. This Product is LEAD-FREE & RoHS Compliance Product.

SPECIFICATIONS

1. D-SUB
- 1.1 Voltage: 250 VAC(RMS) Max.
- 1.2 Current Rating: 3 Ampere per Contact
- 1.3 Contact Resistance: 25 Milliohms Max.
- 1.4 Insulation Resistance: 5000 Megohms Min.
- 1.5 Dielectric Withstanding Voltage: 1000V AC(RMS)
- 1.6 Total Mating Force: 4.0 Kgf Max.
- 1.7 Total Unmating Force: 1.0 Kgf Min.
- 1.8 Operating Temperature: -55°C to +85°C

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X, ±
.X ±
.XX ± 0.25
.XXX ± 0.13
ANG ± 2°

PJECTION

照片框

ORDER INFORMATION

DCD108-PSZ-09-LF

SERIES | | | LEADFREE
09 WAY
CLIP
SEMI GOLD
MALE

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: