



RECOMMENDED P.C.B LAYOUT
INSPECTION DIMENSION:(A)~(G)

NOTES

- MATERIAL:**
Housing:PBT, UL 94V-0, Color:Black.
Terminal:Copper Alloy.
Shell:SPCC.
Boardlock:Copper Alloy.
Screw:Copper Alloy.
- FINISH:**
Terminal:Gold Plated over Nickel at Contact Area.
Tin Plated over Nickel at Solder Area.
Shell:Tin Plated.
Boardlock:Tin Plated.
Screw:Nickel Plated.
- This Product is LEAD-FREE & RoHS Compliance Product.

SPECIFICATIONS

- D-SUB
 - Voltage: 250 VAC(RMS) Max.
 - Current Rating: 3 Ampere per Contact
 - Contact Resistance: 25 Milliohms Max.
 - Insulation Resistance: 5000 Megohms Min.
 - Dielectric Withstanding Voltage: 1000V AC(RMS)
 - Total Mating Force: 9.4 Kgf Max.
 - Total Unmating Force: 1.4 Kgf Min.
 - Operating Temperature: -55°C to +85°C

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±
X ±
.XX ± 0.25
.XXX ± 0.13
ANG ± 1°

PPOJECTION

照片框

ORDER INFORMATION

DCD108-PSZ-25-LF

SERIES LEADFREE
25 WAY
CLIP
SEMI GOLD
MALE

DESCRIPTION: D-SUB 25 MALE CONNECTOR CRIMP TYPE