

RECOMMENDED P.C.B LAYOUT

SPECIFICATIONS

- 1. D-SUB
- 1.1 Operation Voltage: 250 VAC(RMS) Max.
- 1.2 Current Rating: 3 Ampere per Contact
- 1.3 Contact Resistance: 25 Milliohms Max.
- 1.4 Insulation Resistance: 5000 Megohms Min.
- 1.5 Dielectric Withstanding Voltage: 1000 VAC(RMS)
- 1.6 Total Mating Force: 4.0 Kgf Max.
- 1.7 Total Unmating Force: 1.0 Kgf Min.
- 1.8 Operating Temperature: -55°C to +85°C

NOTES

- 1. MATERIAL:
  - Housing:PBT, UL 94V-0, Color:Black.
  - Terminal:Copper Alloy.
  - Shell:SPCC.
  - Boardlock:Copper Alloy.
  - Screw:Copper Alloy.
- 2. FINISH:
  - Terminal:Gold Plated over Nickel at Contact Area.
  - Tin Plated over Nickel at Solder Area.
  - Shell:Tin Plated.
  - Boardlock:Tin Plated.
  - Screw:Nickel Plated.

RoHS Compliant

TOLERANCES ARE



煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4


- X. ±
- .X ±
- .XX ±
- .XXX ±
- ANG ±

PJECTION

照片框

ORDER INFORMATION

DCD150-PSZJ-09-LF



DESCRIPTION: D-SUB 9 FEMALE CONNECTOR CRIMP TYPE