

T:1.6 Dimensions of PC board holes

Tolerance : ±0.05(Printed-top view)

CAT. NO.	PIN	SCHEMATIC
DCJ-D-25	∅2.5	

UNLESS OTHERWISE SPECIFIED, TOLERANCE ON DECIMAL: ±0.3

LTR	PART NAME	QTY	MATERIAL	REMARK
6	COVER	1	PBT 4815	UL-94V0(BLACK)
5	HOUSING	1	PBT 4815	UL-94V0(BLACK)
4	PIN	1	H59(COPPER ALLOY)	Ni PLATED
3	CONTACT FOOT	1	C2680 t=0.40	Ag PLATED
2	SPRING PIECE	1	C5191 t=0.30	Ag PLATED
1	FLAT PIECE	1	C2680 t=0.40	Ag PLATED

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS


UNIT/mm SCALE 1:1

DATE

SIZE A4

X. ±
.X ±
.XX ±
.XXX ±
ANG ±

PJECTION



ORDER INFORMATION

DCJ-D-25-LF
SERIES | LEADFREE
2.5∅
DIP 180°

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: DC POWER JACK