

T:1.6 Dimensions of PC board holes

Tolerance :  $\pm 0.1$  (Printed-top view)

CAT. NO.	PIN	SCHEMATIC
DCJ-D-20	$\phi 2.0$	
DCJ-D-25	$\phi 2.5$	

UNLESS OTHERWISE SPECIFIED, TOLERANCE ON DECIMAL:  $\pm 0.3$

6	COVER	1		
5	CONTACT FOOT	1	BRASS	MB:Cu Cu/Sn PLATED
4	PIN	1	H59 BRASS	MB:Cu Ni PLATED
3	SPRING	1	65Mn STEEL	MB:Cu Cu/Sn PLATED
2	FLAT PIECE	1	H62 BRASS	MB:Cu Cu/Sn PLATED
1	HOUSING	1	PBT/PASS	
LTR	PART NAME	QTY	MATERIAL	REMARK

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm


SCALE 1 : 1

DATE

SIZE A4

P PROJECTION

X,  $\pm$   
.X  $\pm$   
.XX  $\pm$   
.XXX  $\pm$   
ANG  $\pm$



ORDER INFORMATION

DCJ-D-xx-LF  
SERIES T LEADFREE  
20:2.00  
25:2.50  
DIP 180°

DESCRIPTION: DC POWER JACK