



MODEL NO.	DCJ-R15-165
SCHEMATIC	
CENTER PIN	φ1.65mm

\* MATERIAL:  
 CENTRE PIN : BRASS  
 TERMINAL 1 : BRASS  
 TERMINAL 2 : COPPER ALLOY  
 TERMINAL 3 : BRASS  
 HOUSING : PA66

SPECIFICATIONS

- 1 Insulation resistance of adjacent open terminals shall not be less than 50 Megohms when measured with 500 Volts resistance meter.
- 2 Connector shall withstand 500 Volts (RMS) between adjacent open terminal for one minute.
- 3 Contact resistance of normally closed terminals shall not exceed 0.03 ohms when measured at a current of one Ampere by Voltage drop method.
- 4 Connector shall withstand 5,000 cycles of insertions and withdrawal with testing plug , contact resistance shall not exceed 0.1 ohm.

DCJ-R15-165-LF  
 LEADFREE RoHS Compliant



PART NO. DCJ-R15-165	
DWG NO. DCJ-R15-165	
FILE NO.	CHECKED BY CY
UNIT / mm	DRAWING BY
SCALE 1:1	PROJECTION

TOLERANCES ARE
X. ±
.X ±
.XX ±
.XXX ±
ANG

DESCRIPTION:	
AREA	REVISIONS
	DATE

煜倫股份有限公司