



MODEL NO.	DCJ-R20MM10A-xx
SCHEMATIC	2 1(5)
CENTER PIN	φ2.0mm φ2.5mm

### SPECIFICATION

1. Contact resistance :  $\leq 30m\Omega$
2. Insulation resistance :  $\geq 100M\Omega$
3. Withstand voltage : 500VAC
4. Insertion and extraction force : 5-30N
5. life test : 5,000 cycles

NO.	DESCRIPTION	QTY	MATERIAL	PLATING
⑥	HOUSING	1	PA9T	
⑤	SHELL	1	PHOSPHOR BRONZE / IRON	Ni-Plating
④	COAT	1	SUS	
③	PEG	1	BRASS	
②	PIN	1	ZINC ALLOY	Ni-Plating
①	SPRING PIECE	1	PHOSPHOR BRONZE	Ag-Plating
NO.	DESCRIPTION	QTY	MATERIAL	PLATING

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PJECTION

Up to 5 ±0.2  
Above 5 ~ 15 ±0.3  
Above 15 ~ 30 ±0.4  
Above 30 ~ 50 ±0.5  
Angle ±0.3°

照片框

### ORDER INFORMATION

DCJ-R20MM10A-xx-LF  
SERIES | | | LEADFREE  
20:2.0Ø  
25:2.5Ø  
10Amp  
DIP 90° METAL FOOT  
POST 2.75mm

DESCRIPTION: DC JACK