



P.C.B LAYOUT
TOP VIEW

SPECIFICATION

1. Rating : DC 30V 0.5A;
2. Contact resistance: $\leq 0.03 \Omega$;
3. Insulation resistance: $\geq 100M \Omega$ (DC250V);
4. Withstand voltage: 500VAC ;
5. Insertion and extraction force: 3-20N;
6. life test: 5,000 cycles.

CAT. NO.	PIN	SCHEMATIC
DCJ-RK-10	$\phi 1.0$	
DCJ-RK-13	$\phi 1.3$	
DCJ-RK-165	$\phi 1.65$	

NO.	DESCRIPTION	QTY	MATERIAL	REMARK
6	PIN	1	BRASS	Ni-Plating
5	CURVE PIECE	1	BRASS	Ag-Plating
4	FLAT PIECE	1	BRASS	Ag-Plating
3	SPRING PIECE	1	SUS301	Ag-Plating
2	COVER	1	PBT	
1	HOUSING	1	PBT	

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X. ±
.X ±
.XX ±
.XXX ±
ANG ±

PJECTION

照片框

ORDER INFORMATION

DCJ-RK-(10)(13)(165)-LF
LEADFREE
SERIES
10:1.0Ø
13:1.3Ø
165:1.65Ø
KINK
DIP 90°

DESCRIPTION: