



T:1.6 Dimensions of PC board holes
Tolerance : ±0.1(Printed-top view)

CAT. NO.	PIN	SCHEMATIC
DCJ-RKPN-20	ø2.0	

UNLESS OTHERWISE SPECIFIED, TOLERANCE ON DECIMAL: ±0.3

LTR	PART NAME	QTY	MATERIAL	REMARK
6	HOUSING	1	PBT 4815	UL-94V0(BLACK)
5	COVER	1	PBT 4815	UL-94V0(BLACK)
4	PIN	1	C2680	MB:Cu Cu/Sn PLATED
3	SHUNT TERMINAL	1	C2680 t=0.5	MB:Cu Cu/Sn PLATED
2	TIP SPRING	1	C5191 t=0.25	MB:Cu Cu/Sn PLATED
1	CENTER PIN TERMINAL	1	C2680 t=0.5	MB:Cu Cu/Sn PLATED

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT/mm SCALE 1:1

DATE

SIZE A4

X, ±
.X ± 0.30
.XX ± 0.20
.XXX ±
ANG ±

PJECTION

照片框

ORDER INFORMATION

DCJ-RKPN-20-LF
SERIES | | LEADFREE
| | 2.0Ø
| | PANEL
| | KINK
| | DIP 90°

DESCRIPTION: