



PCB LAYOUT
TOP VIEW

| CAT. NO. | PIN | SCHEMATIC |
|-------------|------|-----------|
| DCJ-RLTP-20 | ø2.0 | |
| DCJ-RLTP-25 | ø2.5 | |

| LTR | PART NAME | QTY | MATERIAL | REMARK |
|-----|----------------|-----|-------------|----------------|
| 6 | TERMINAL | 1 | C2680 t=0.5 | Sn PLATED |
| 5 | SHUNT TERMINAL | 1 | C2680 t=0.5 | Sn PLATED |
| 4 | TIP TERMINAL | 1 | C5191 t=0.3 | Sn PLATED |
| 3 | PIN | 1 | BRASS BAR | Ni PLATED |
| 2 | COVER | 1 | PBT | UL-94V0(BLACK) |
| 1 | BODY | 1 | PBT | UL-94V0(BLACK) |

UNLESS OTHERWISE SPECIFIED, TOLERANCE ON DECIMAL: ±0.3

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

X.±

CHECKED BY GENIUS

.X±

UNIT / mm

SCALE 1:1

.XX±

DATE

.XXX±

ANG±

煜倫股份有限公司

www.morethanall.com

SIZE A4

PJECTION

照片框

ORDER INFORMATION

DCJ-RLTP-xx-LF
SERIES | | | | | LEADFREE
20:2.00
25:2.50
DIP 90° | | | | | POST
TILTED
LOCK

DESCRIPTION: DC POWER JACK