



T:1.6 Dimensions of PC board holes
Tolerance: ±0.05(Printed-top view)

| CAT. NO. | PIN | SCHEMATIC |
|------------|------|-----------|
| DCJ-RPN-20 | ø2.0 | |
| DCJ-RPN-25 | ø2.5 | |

| LTR | PART NAME | QTY | MATERIAL | REMARK |
|-----|---------------------|-----|-------------------|--------------|
| 6 | HOUSING | 1 | PA66 | BLACK |
| 5 | COVER | 1 | PA66 | BLACK |
| 4 | CENTER PIN | 1 | H59(COPPER ALLOY) | Cu/Sn PLATED |
| 3 | SHUNT TERMINAL | 1 | C2680 t=0.35 | Ag PLATED |
| 2 | TIP SPRING | 1 | C5191 t=0.25 | Ag PLATED |
| 1 | CENTER PIN TERMINAL | 1 | C2680 t=0.35 | Ag PLATED |

UNLESS OTHERWISE SPECIFIED, TOLERANCE ON DECIMAL: ±0.3

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X. ± 0.30
.X ± 0.30
.XX ± 0.20
.XXX ± 0.10
ANG ± 1°

PJECTION

照片框

ORDER INFORMATION

DCJ-RPN-xx-LF
SERIES | LEADFREE
20:2.00
25:2.50
PANEL
DIP 90°

DESCRIPTION: DC POWER JACK