



BOTTOM VIEW

- Pb :less than 40000ppm
 Cd :less than 75ppm
- 1.Dielectric strength:AC 500V/1 minute.
 - 2.Insulation resistance :100MΩ or over.(DC 500V)
 - 3.Contact resistance :30mΩ or less.
 - 4.Extraction force :0.3~3Kg.

4	190-089	DIELECTRIC	PBT	BLACK	1
3	170-236	Terminal	Phosphor Bronze	AG	1
2	119-147	SLEEVE	BRASS	NI	1
1	152-045	PIN	ALLOY	AG	1
ITEM	DRAWING NUMBER	PART NAME	MATERIAL	PLATED	Q'TY

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X.±
 .X±
 .XX±
 .XXX±
 ANG±

P PROJECTION

照片框

ORDER INFORMATION

DCJ-S-5522-LF
 SERIES | LEADFREE
 ID:2.2Ø
 OD:5.5Ø
 SOLDER

DESCRIPTION: 5.5X2.1DC JACK (180°)