



CAT NO.	PIN	SCHEMATIC
DCJ-SPBT8-20	$\phi 2.0$	
DCJ-SPBT8-25	$\phi 2.5$	

6	HOUSING	1	PA66	
5	AXIS SUPPORT	1	BRASS	MB:Cu Ni PLATED
4	PIN	1	H59 BRASS	MB:Cu Ni PLATED
3	SPRING	1	BRONZE	MB:Cu Cu/Sn PLATED
2	CURVE PIECE	1	H62 BRASS	MB:Cu Cu/Sn PLATED
1	FLAT PIECE	1	H62 BRASS	MB:Cu Cu/Sn PLATED
LTR	PART NAME	QTY	MATERIAL	REMARK

UNLESS OTHERWISE SPECIFIED, TOLERANCE ON DECIMAL: ± 0.3

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

RoHS Compliant

TOLERANCES ARE

DRAWING BY CY	X. ± 0.30
CHECKED BY GENIUS	.X ± 0.30
UNIT / mm	.XX ± 0.20
SCALE 1 : 1	.XXX ± 0.10
DATE	ANG $\pm 1^\circ$

SIZE A4

PJECTION

照片框

ORDER INFORMATION

DCJ-SPBT8-xx-LF
SERIES | | | LEADFREE
20:2.00
25:2.50
SOLDER | | | THREAD 0.8mm
BACK
PANEL

DESCRIPTION: DC POWER JACK