



UNLESS OTHERWISE SPECIFIED, TOLERANCE ON DECIMAL:  $\pm 0.3$

6	COVER	1	PF	
5	HOUSING	1	PBT 4815	UL-94V0 (BLACK)
4	CENTER PIN	1	C2680	Sn PLATED
3	SHUNT TERMINL	1	C2680	Ag PLATED
2	TIP SPRING	1	C5191	Ag PLATED
1	CENTER PIN TERMINAL	1	C2680	Ag PLATED
LTR	PART NAME	QTY	MATERIAL	REMARK

**RoHS Compliant**

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

P PROJECTION

X.  $\pm$   
.X  $\pm$   
.XX  $\pm$   
.XXX  $\pm$   
ANG  $\pm$



**ORDER INFORMATION**

DCJ-SPC-25-LF  
SERIES | T | LEADFREE  
2.5 $\phi$   
C TYPE  
PANEL  
SOLDER

DESCRIPTION: DC POWER JACK

煜倫股份有限公司

www.morethanall.com