



L SIZE:
9.5MM
ID SIZE:
2.1MM OR 2.5MM

SPECIFICATION

Dielectric strength: AC500 1 Minute
 Insulation resistance: 100M ohm at 500VDC
 Contact resistance: 30m ohm Max
 Rating: 3A

TOLERANCES	
0.5MM-5MM	=±0.2MM
5MM-30MM	=±0.4MM
30MM-120MM	=±0.6MM
120MM-315MM	=±1.0MM
315MM-1000MM	=±1.6MM
1000MM-2000MM	=±2.4MM

No.	Description	Material	Qty
1	HexagonHandle	PlasticPE208	1
2	Contact	C2680copper,Nickel	1
3	Plug	C3604AlloyCopper,Nickel	1
4	Blacktip	Derlin	1
5	InsideInsulation	Derlin+Fiber	2

2.1X5.5X9.5MM
 2.5X5.5X9.5MM

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES
煜倫股份有限公司
www.morethanall.com

DRAWING BY CY		X. ± .X ± .XX ± .XXX ± ANG ±
CHECKED BY GENIUS		
UNIT / mm	SCALE 1 : 1	
DATE		
SIZE A4	P PROJECTION	



ORDER INFORMATION

DCP-A-55xx-LF
 SERIES | LEADFREE
 21: ID: 2.1Ø
 25: ID: 2.5Ø
 OD: 5.5Ø
 ASSEMBLY

DESCRIPTION: DC PLUG W/HEXAGON PLASTIC HANDLE