



Dielectric Strength: AC500V 1 minute  
 Insulation resistance: 100M ohm min.(AT 500V DC)  
 Contact resistance: 30m ohm Max  
 Rating: 2A 18V DC

| NO | PART NAME(品名) | MATERIAL(材質) | FINISHED(外觀) | Q'TY |
|----|---------------|--------------|--------------|------|
| 1  | DC頭金屬本體       | C3604 COPPER | 鍍鎳NICKEL     | 1    |
| 2  | 塑膠殼           | PE           | 黑色BLACK      | 1    |
| 3  | 尾套塑膠          | PVC          | 黑色BLACK      | 1    |
| 4  | DC頭黑色絕緣       | POM          | 黑色BLACK      | 1    |
| 5  | DC頭尾部白色絕緣     | ABS          | 白色WHITE      | 1    |
| 6  | 焊線孔           | C2680 COPPER | NICKEL       | 1    |
| 7  | 線夾            | C2680 COPPER | NICKEL       | 1    |

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
 PCB CONNECTORS  
 Cable ASSEMBLIES

DRAWING BY CY

X, ±

CHECKED BY GENIUS

.X ± 0.30

UNIT / mm

SCALE 1 : 1

.XX ± 0.20

.XXX ± 0.10

ANG ±

DATE

SIZE A4

P PROJECTION

照片框

ORDER INFORMATION

DCP-ARS-5521-LF  
 SERIES ID: 2.10 LEADFREE  
 SCW OD: 5.50  
 90° ASSEMBLY

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: 90度DC頭 ASSEMBLY TYPE