



Dielectric Strength: AC500V 1 minute
 Insulation resistance: 100M ohm min.(AT 500V DC)
 Contact resistance: 30m ohm Max
 Rating: 2A 18V DC

NO	PART NAME(品名)	MATERIAL(材質)	FINISHED(外觀)	Q'TY
1	DC頭金屬本體	C3604 COPPER	鍍鎳NICKEL	1
2	塑膠殼	PE	黑色BLACK	1
3	尾套塑膠	PVC	黑色BLACK	1
4	DC頭黑色絕緣	POM	黑色BLACK	1
5	DC頭尾部白色絕緣	ABS	白色WHITE	1
6	焊線孔	C2680 COPPER	NICKEL	1
7	線夾	C2680 COPPER	NICKEL	1

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

DRAWING BY CY

X, ±

CHECKED BY GENIUS

.X ± 0.30

UNIT / mm

SCALE 1:1

.XX ± 0.20

DATE

.XXX ± 0.10

ANG ±

煜倫股份有限公司

www.morethanall.com

SIZE A4

P PROJECTION

照片框

ORDER INFORMATION

DCP-ARS-5525-LF
 SERIES | | | LEADFREE
 ID:2.5Ø
 OD:5.5Ø
 SCW
 90°
 ASSEMBLY

DESCRIPTION: 90度DC頭 ASSEMBLY TYPE