



Follow RoHs Standard

1. Dielectric strength: AC 500V/1 minute.
2. Insulation resistance: 100MΩ Min. (at 500V DC)
3. Contact resistance: 30mΩ Max.
4. Rating: 18V, 2A.

△	7	190-067	外殼	ABS		1
	6	170-184	彈片 B	黃銅	鍍鎳	1
	5	170-185	彈片 A	黃銅	鍍鎳	1
△	4	176-003	墊片	PBT(HB)		1
	3	119-106	鎖牙套管	黃銅	鍍鎳	1
△	2	119-105	螺帽	黃銅	鍍鎳	1
	1	150-217	5.5X2.1DC 插頭		鍍鎳	1
	項目	圖面號碼	零件名稱	材料	處理	數量

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1:1

DATE

SIZE A4

P PROJECTION

X. ±
.X ±
.XX ±
.XXX ±
ANG ±



ORDER INFORMATION

DCP-AS-5521S-LF
SERIES | ID: 2.1Ø | LEADFREE
| | SHORT
| | OD: 5.5Ø
SCREW ASSEMBLY

DESCRIPTION: 5.5X2.1DC 插頭(內鎖牙裝配式) 9.5mm

煜倫股份有限公司

www.morethanall.com