



NOTE:

1. CENTER CONDUCTOR CONNECTION FORCE
 $\phi 0.8 \pm 0.002$ PIN GAUGE MEASURE AFTER 2 TIMES OPERATION
 INSERTION FORCE : 1.0 kgf MAX.
 WITHDRAMAL FORCE : 0.1kgf MIN.

2. VOTAGE PROOF : AC500V / 1MIN
3. INSURATION RESISTANCE : DC500V / 100m Ω OR MORE
4. CONTACT RESISTANCE : 30m Ω OR LESS

5		
4	POM	BLACK
3	-BRONZE	P Sn
2	BRASS	NICKEL
1	PBT	BLACK
材料	材質	處理

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4 PPROJECTION

X. \pm
 .X \pm
 .XX \pm
 .XXX \pm
 ANG \pm

照片框

ORDER INFORMATION

DCP-S-3209L-LF
 SERIES | LEADFREE
 | LONG
 | 3.2X0.90
 SOLDER

DESCRIPTION: DC PIUG $\phi 3.2 \times \phi 0.9 \times 20.2$