



PIN OUT

P1	P2
1	S/T BLACK / WHITE
2	S/T BLACK

ELECTRONIC TEST CONDITION:
 100% OPEN SHORT & MISWIRE TEST,
 CONDUCTIVE RESISTANCE:5 Ω /MAX
 INSULATION RESISTANCE:10M Ω /MIN.AT DC 300V

PART LIST:ROHS

ITEM	STANDARD SPECIFICATION	Q'TY	UNIT
1	CABLE:UL2468 20AWG*2F OD:1.8*3.6MM #BLACK L=1800MM	PCS	1
2	CONN:5510-1H-22.5MM	PCS	1
3	PVC 45P #BLACK	G	5

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X. ±
 .X ±
 .XX ±
 .XXX ±
 ANG ±

P PROJECTION

照片框

ORDER INFORMATION

DCX1-5510R20-M6F-LF

SERIES LEADFREE

6F
 MALE
 20 AWG
 90°
 5.5x1.0mm

DESCRIPTION: