



A	線色	B
1	紅	TIN
2	黑	TIN

NOTES:

1. ALL DIMENSIONS ARE "mm".
2. THE PRODUCT MUST BE COMPLY WITH THE DIRECTIVE OF ROHS.

ELECTRICAL TESTING:

1. 100% OPEN/SHORT TEST
2. CONTACT RESISTANCE: 5mΩ
3. INSULATION RESISTANCE: 5MΩ Min

NO.	ITEM.	DESCRIPTION	Q'TY	UL/CSA No.
1	WIRE:	UL2468 #22*2C 黑紅並線	1pcs	
2	CONN:	DC PLUG $\phi 5.5 \times \phi 2.5 \times L: 20.5$ P/N: 5525D205-1M00-L2	1pcs	
3	外模料:	PVC 45P 黑色 模號: GH-233	4.2G	
4	SHRINK TUBE:	1.0 ϕ *8mm 黑 F32	1pcs	
5	保險絲殼:	P-E80401C, P-E80401M	1set	
6	保險絲:	5A 250V $\phi 6.0 \times 30$	1pcs	
7	TERMINAL:	E80401BS-0	2pcs	
8	彈簧:	L=25mm 5.5 ϕ	1pcs	

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1:1

DATE

SIZE A4

X. \pm
.X \pm
.XX \pm
.XXX \pm
ANG \pm

P PROJECTION

照片框

ORDER INFORMATION

DCX1-552522FH-M1M-LF

SERIES | LEADFREE
1000mm
MALE
FUSE HOLDER
22 AWG
5.5X2.5mm

DESCRIPTION: