



Material & Finish

SHELL:

Steel
 Front Shell Nickel Plated
 Back Shell Tin Plated

PIN CONTACT:

Brass
 All Gold Flash Plated

INSULATOR:

PBT & Glass-fibre reinforced
 UL-94-V0 White

HEX SCREW

Copper Alloy, Nickel Plated

BRACKET

Copper Alloy, Tin Plated

CURRENT RATING:

3 Amp

CONTACT RESISTANCE:

20mΩ Max

DIELECTRIC STRENGTH:

1000VAC for one minute

INSULATOR RESISTANCE:

1000MΩ Min. (at 500VDC)

TEMPERATURE:

-55°C to +85°C

RECOMMEND PCB LAYOUT

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X. ± 0.40

.X ± 0.30

.XX ± 0.20

.XXX ±

ANG ± 3°

PJECTION

照片框

ORDER INFORMATION

DD-PGZ075-09-LF

SERIES
 LEADFREE
 09WAY
 HIGH 7.5mm
 Z-BRACKET
 FULL GOLD
 MALE

DESCRIPTION: D-SUB PCB S/T TYPE 9PIN MALE BACK RIVET 7.5 BRACKET