



**Material & Finish**

**SHELL:**

Steel  
 Front Shell Nickel Plated  
 Back Shell Tin Plated

**PIN CONTACT:**

Brass  
 Gold Flash Plated

**INSULATOR:**

PBT & Glass-fibre reinforced  
 UL-94-V0 Black

**HEX SCREW**

Copper Alloy, Nickel Plated

**BRACKET**

Copper Alloy, Tin Plated

**CURRENT RATING:**

3 Amp

**CONTACT RESISTANCE:**

20mΩ Max

**DIELECTRIC STRENGTH:**

1000VAC for one minute

**INSULATOR RESISTANCE:**

1000MΩ Min. (at 500VDC)

**TEMPERATURE:**

-55°C to +85°C

Positions	A	B	C	D
09	16.92	24.99	30.81	19.28
15	25.25	33.32	39.14	27.65
25	38.96	47.04	53.04	41.30
37	55.42	63.50	69.32	57.44

**RoHS Compliant**

TOLERANCES ARE

**MORETHANALL**  
 PCB CONNECTORS  
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1:1

DATE

SIZE A4

X ± 0.50

.X ± 0.30

.XX ± 0.20

.XXX ±

ANG ± 3°

PJECTION

照片框

**ORDER INFORMATION**

DD-PSZJM26BK-xx-LF  
 SERIES | M2.6 JACKSCREW | LEADFREE  
 | | BLACK | 09-37 WAY  
 MALE SEMI GOLD CLIP

DESCRIPTION: D-SUB PCB S/T TYPE MALE BACK RIVET 6.0mm BRACKET FRONT LOCK 5.8 HEX-SCREW