



Note:

1. Material:

- 1.1 Insulator: High Temperature thermoplastic with g.f,UL94V-0
- 1.2 Contact: Copper alloy,t=0.20mm
- 1.3 Shell: Spcc,t=0.30mm

2. Specification:

- 2.1 Current rating: 5 A Max.
- 2.2 Dielectric withstanding voltage: 750 v(ac) for 1 min.
- 2.3 Contact resistance: 30 mΩ Max.
- 2.4 Insulation resistance: 1000MW Min.
- 2.5 Total mating force: 7.0 Kgf Max.
- 2.6 Total unmating forc: 1.5 Kgf Min.
- 2.7 Temperature range: -55°C~85°C

PART NO	A±0.25	B±0.20	C±0.20	D±0.20	E±0.20	F±0.25	G±0.25	H±0.25	I±0.10	J±0.25	K±0.25
DDL-PGZ-09	30.81	24.99	16.92	8.38	16.90		12.55	2.77	2.84		
DDL-PGZ-15	39.25	33.32	25.25	8.38	16.90		12.55	2.77	2.84		
DDL-PGZ-19	44.80	38.86	30.60	8.38	16.90		12.55	2.77	2.84		
DDL-PGZ-23	50.30	44.30	35.90	8.38	16.90		12.55	2.77	2.84		
DDL-PGZ-25	53.04	47.04	38.96	8.38	16.90		12.55	2.77	2.84		
DDL-PGZ-37	69.50	63.50	55.42	8.38	16.90		12.55	2.77	2.84		

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

P PROJECTION

X, ±
.X ±
.XX ±
.XXX ±
ANG ±

照片框

ORDER INFORMATION

DDL-PGZ-xx-LF
SERIES | | LEADFREE
| | 09~37WAY
| | CLIP
| | GOLD
| | MALE

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: