

Recomended PCB Layout

Specifications

Contact Resistance:  $\leq 30m$  max. at DC 100mA  
 Insulator Resistance:  $1000M$  min. at DC 500V  
 Current Rating: 5 AMP  
 Dielectric Withstanding Voltage: AC 1000V For 1 minute  
 Operating Temperature:  $-55^{\circ}C \sim +105^{\circ}C$   
 Contact: Brass  
 Housing: PBT & 30% Glass Fiber (UL 94V-0)

Dimension

Positon	A	B	C	D
09	30.81	24.99	16.92	16.96
15	39.14	33.32	25.50	25.18
25	53.04	47.04	38.96	39.12
37	69.32	63.50	55.42	55.68

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
 PCB CONNECTORS  
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS


UNIT / mm SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X. ±  
 .X ±  
 .XX ±  
 .XXX ±  
 ANG ±



ORDER INFORMATION

DDM-PNJ-xx-LF  
 SERIES | | | LEADFREE  
 | | | 09-37WAY  
 | | | JACKSCRW  
 | | | NUT  
 | | | MALE

DESCRIPTION: D-SUB DIP STRAIGHT TYPE W/O METAL REAT SHELL