


RECOMMENDED PCB LAYOUT
 GENERAL TOLERANCE ± 0.05
 WITHOUT BOSS WITHOUT FITTING NAIL

NOTES:

1. MATERIAL:
 - 1.1 HOUSING: THERMOPLASTIC, HIGH TEMP., UL94V-0; COLOR IS NATURAL.
 - 1.2 CONTACT: COPPER ALLOY
2. FINISH:
 - 2.1 CONTACT: GOLD FLASH OVER ALL
50u" MIN. NICKEL UNDERPLATING OVERALL.
3. IR REFLOW CAPABLE TO 260°C



CKT	DIM A	DIM B	DIM C	DIM D	DIM E	DIM F	MYLAR-A H	MYLAR-B H
010	4.7	2.00	2.80	3.20		2.8	3.0	3.0
014	5.7	3.00	3.80	4.20		3.8	3.0	3.0
020	7.2	4.50	5.30	5.70		5.3	5.0	5.0
024	8.2	5.50	6.30	6.70		6.3	5.0	5.0
030	9.7	7.00	7.80	8.20		7.8	6.0	6.0
032	10.2	7.50	8.30	8.70		8.3	6.0	6.0
036	11.2	8.50	9.30	9.70		9.3	6.0	6.0
040	12.2	9.50	10.30	10.70		10.3	6.0	6.0
050	14.7	12.00	12.80	13.20		12.8	6.0	6.0
060	17.2	14.50	15.30	15.70		15.3	6.0	6.0
080	22.2	19.50	20.30	20.70		20.3	6.0	6.0

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X, ± 0.50
 X, ± 0.25
 .XX, ± 0.15
 .XXX, ± 0.10
 ANG $\pm 2^\circ$

P PROJECTION

照片框

ORDER INFORMATION

DF12-P23XC-xxx-LF

SERIES

|

|

|

|

LEADFREE

010-080 WAY

MYLAR

NON POST

UNMATED HIGH 2.30mm

MALE

DESCRIPTION: 0.5mm B-T-B CONNECTOR PLUG D/R S/T SMT TYPE

煜倫股份有限公司

www.morethanall.com