





NOTES:

1. MATERIAL:
 - 1.1 HOUSING: THERMOPLASTIC, HIGH TEMP., UL94V-0; COLOR IS NATURAL.
 - 1.2 CONTACT: COPPER ALLOY
2. FINISH:
 - 2.1 CONTACT: GOLD FLASH OVER ALL
50u" MIN. NICKEL UNDERPLATING OVERALL.
3. IR REFLOW CAPABLE TO 260°C



RECOMMENDED PCB LAYOUT
GENERAL TOLERANCE ±0.05



CKT	DIM A	DIM B	DIM C	DIM D	DIM E	DIM F	MYLAR SIZE
010	4.6	3.15	2.70	2.00		2.8	3.00
014	5.6	4.15	3.70	3.00		3.8	3.00
020	7.1	5.65	5.20	4.50		5.3	3.00
024	8.1	6.65	6.20	5.50		6.3	6.00
030	9.6	8.15	7.70	7.00		7.8	6.00
032	10.1	8.65	8.20	7.50		8.3	6.00
036	11.1	9.65	9.20	8.50		9.3	6.00
040	12.1	10.65	10.20	9.50		10.3	6.00
050	14.6	13.15	12.70	12.00		12.8	6.00
060	17.1	15.65	15.20	14.50		15.3	6.00
080	22.1	20.65	20.20	19.50		20.3	6.00

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X. ± 0.50
.X ± 0.25
.XX ± 0.15
.XXX ± 0.10
ANG ± 2°

PPOJECTION

照片框

ORDER INFORMATION

DF12-S07XC-xxx-LF

SERIES | | | LEADFREE
| | | 010-080 WAY
| | | MYLAR
| | | NON POST
| | | UNMATED HIGH 0.7mm
| | | FEMALE

DESCRIPTION: 0.5mm B-T-B CONNECTOR RCPT D/R S/T SMT TYPE

煜倫股份有限公司

www.morethanall.com