

SPECIFICATIONS

Current Rating : 1A AC,DC

Voltage Rating : 100V AC,DC

Temperature Range : -25°C~+85°C

Contact Resistance : 20mΩ Max.

Insulation Resistance : 500MΩ Min.

Withstanding Voltage : 500V AC/Min.

Pin Material : Brass/Tin-plated

Solder Tabs : Phosphor Bronze/Tin-plated

Material : Nylon 6T, UL94V-0

Ordering Information & Dimensions

PART NO.	Dimensions		
	A	B	C
DF13-VP-1X02	1.25	4.15	6.25
DF13-VP-1X03	2.50	5.40	7.50
DF13-VP-1X04	3.75	6.65	8.75
DF13-VP-1X05	5.00	7.90	10.00
DF13-VP-1X06	6.25	9.15	11.25
DF13-VP-1X07	7.50	10.40	12.50
DF13-VP-1X08	8.75	11.65	13.75
DF13-VP-1X09	10.00	12.90	15.00
DF13-VP-1X10	11.25	14.15	16.25
DF13-VP-1X11	12.50	15.40	17.50
DF13-VP-1X12	13.75	16.65	18.75
DF13-VP-1X13	15.00	17.90	20.00
DF13-VP-1X14	16.25	19.15	21.25
DF13-VP-1X15	17.50	20.40	22.50

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS


UNIT/mm SCALE 1:1

DATE

SIZE A4

X.±
.X±
.XX±
.XXX±
ANG±

PJECTION



ORDER INFORMATION

DF13-VP-1Xxx-LF

SERIES | LEADFREE
1X02:02WAY
1X15:15WAY
POST
180°SMT

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: 1.25mm Wire-to-Board Header SMD 180° TYPE