



**Dimensional Information:**

Circuits	Dimensions		Qty/Reel	Circuits	Dimensions		Qty/Reel
	A	B			A	B	
4	8.35	—	1000	24	20.85	13.75	1000
6	9.60	2.50	1000	26	22.10	15.00	1000
8	10.85	3.75	1000	28	23.35	16.25	1000
10	12.10	5.00	1000	30	24.60	17.50	1000
12	13.35	6.25	1000	32	25.85	13.75	1000
14	14.60	7.50	1000	34	27.10	15.00	1000
16	15.85	8.75	1000	36	28.35	16.25	1000
18	17.10	10.00	1000	38	29.60	17.50	1000
20	18.35	11.25	1000	40	30.85	17.50	1000
22	19.60	12.50	1000				

**Material:**

- \* Insulator: Nylon 6T UL 94V-0 (Milky Yellow)
- \* Contact Post: Phosphor Bronze, Matte Tin Plated.
- \* Solder Tab: 0.20mm<sup>t</sup> Brass, Matte Tin Plated.

**RoHS Compliant**



煜倫股份有限公司

www.morethanall.com

DRAWING BY CY  
 CHECKED BY GENIUS  
 UNIT / mm SCALE 1 : 1  
 DATE  
 SIZE A4 PPROJECTION

**TOLERANCES ARE**

- X, ±
- .X ±
- .XX ±
- .XXX ±
- ANG ±

照片框

**ORDER INFORMATION**

DF13-VX-2Xxx-LF  
 SERIES | LEADFREE  
 2X02:04WAY  
 2X20:40WAY  
 NON POST  
 180°SMT

DESCRIPTION: