



E/E1	TUBE	$\phi 8.0 / \phi 4.0$	1/1PCS
D	BRAID	168C/0.12T	1PCS
C/C1	WIRE	UL1571 28# 0.6 / UL1571 28# 0.8	28/8PCS
B4	TERMINAL	DF14-T-28 OR EQU	8PCS
A4	HOUSING	DF14-H-09 1.25PITCH OR EQU	1PCS
B3	TERMINAL	PH-T-24 OR EQU	4PCS
A3	HOUSING	PH-H-04 2.0PITCH OR EQU	1PCS
B2	TERMINAL	DF13-T-26 OR EQU	28PCS
A2	HOUSING	DF13-H-2X20 1.25C	1PCS
B1	TERMINAL	FIX-TG-30 OR EQU	28PCS
A1	HOUSING	FIX-HL-30 (FIX-HL) 1.0PITCH OR EQU	1PCS
NO	DESCRIPTION	SPECIFICATION	Q'ty

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±

.X ±

.XX ±

.XXX ±

ANG ±

PJECTION

照片框

ORDER INFORMATION

DF13FIXL-B203028-A30CB

SERIES

300mm

FEMALE TO MALE

28 AWG

40 TO 30 WAY

煜倫股份有限公司

www.morethanall.com

DESCRIPTION:

CONN1				CONN2
PIN NO.		FUNCTION	COLOR	PIN NO.
1	twist	LVDS0_Z_D0-	BLUE	7
2	twist	LVDS0_Z_D0+	WHITE	9
3	twist	LVDS0_Z_D1-	BLUE	13
4	twist	LVDS0_Z_D1+	WHITE	15
5	twist	LVDS0_Z_D2-	BLUE	19
6	twist	LVDS0_Z_D2+	WHITE	21
7		GND	BLACK	23
8	twist	LVDS0_Z_CK-	BLUE	25
9	twist	LVDS0_Z_CK+	WHITE	27
10	twist	LVDS0_Z_D3-	BLUE	31
11	twist	LVDS0_Z_D3+	WHITE	33
12	twist	LVDS1_Z_D0-	BLUE	8
13	twist	LVDS1_Z_D0+	WHITE	10
14		GND	BLACK	12
15	twist	LVDS1_Z_D1-	BLUE	14
16	twist	LVDS1_Z_D1+	WHITE	16
17		GND	BLACK	18
18	twist	LVDS1_Z_D2-	BLUE	20
19	twist	LVDS1_Z_D2+	WHITE	22
20	twist	LVDS1_Z_CK-	BLUE	26
21	twist	LVDS1_Z_CK+	WHITE	28
22	twist	LVDS1_Z_D3-	BLUE	32
23	twist	LVDS1_Z_D3+	WHITE	34
24		GND	BLACK	30
25		NC		-
26		NC		-
27		VDD	RED	4
28		VDD	RED	3
29		VDD	RED	2
30		VDD	RED	1

CONN3				CONN4
PIN NO.		FUNCTION	COLOR	PIN NO.
1		VDD	RED	1, 2, 3
2		EN	WHITE	8
3		PWM	GREEN	9
4		GND	BLACK	5, 6, 7

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±
.X ±
.XX ±
.XXX ±
ANG ±

PPOJECTION 

照片框

ORDER INFORMATION

DF13FIXL-B203028-A30CB

SERIES

300mm

FEMALE TO MALE

28 AWG

40 TO 30 WAY

DESCRIPTION: