



PIN OUT

P1	P2	P3	COLOR
7	1		RED
25	2		RED
10	4		BLACK
11	5		WHITE
12	6		BLUE
13	7		BLACK
14	8		WHITE
15	9		BLUE
16	10		BLACK
17	11		WHITE
18	12		BLUE
19	13		BLACK
20	14		WHITE
21	15		BLUE
22	16		BLACK
23	17		WHITE
24	18		BLUE
30	19		BLACK
5		1	RED
6		2	RED
1		3	BLACK
2		4	BLACK
3		5	ORANGE
4		6	YELLOW

RoHS Compliant

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES
 煜倫股份有限公司
 www.morethanall.com

DRAWING BY CY		TOLERANCES ARE X, ± .X ± .XX ± .XXX ± ANG ±
CHECKED BY GENIUS		
UNIT / mm	SCALE 1 : 1	
DATE		
SIZE A4	PJECTION	

照片框

ORDER INFORMATION

DF19FIXPH-20300628L2-A30C-LF			
SERIES			LEADFREE
			300mm
			FEMALE TO MALE
			LATCH
			28 AWG
			30 TO 20/06 WAY

DESCRIPTION: WIRE HARNESS

1. P1 : 1.0mm PITCH CRIMP TERMINAL AND HOUSING JAE **FIX-HL-30** or EQUIVALENT
2. P2 : 1.0mm PITCH CRIMP TERMINAL AND HOUSING HRS Df19 -HM-20 or EQUIVALENT
3. P3 : 2.0mm PITCH CRIMP TERMINAL AND HOUSING **PH-H-06** or EQUIVALENT
4. P4,P5 : INSIDE EXPANDABLE SLEEVING IN COPPER BRAID OVER THE WIRE AND OUTSIDE COVER ACETATE CLOTH TAPE COLOR=BLACK
5. WIRE IS UL(1571) 28AWG 80°C 30V PVC JACKET

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X, ±
.X ±
.XX ±
.XXX ±
ANG ±

P PROJECTION 

照片框

ORDER INFORMATION

DF19FIXPH-20300628L2-A30C-LF

SERIES

LEADFREE

300mm

FEMALE TO MALE

LATCH

28 AWG

30 TO 20/06 WAY

DESCRIPTION: WIRE HARNESS