



| PIN OUT |           |
|---------|-----------|
| 1       | 1 BLACK   |
| 2       | 2 WHITE   |
| 3       | 3 BROWN   |
| 4       | 4 WHITE   |
| 5       | 5 RED     |
| 6       | 6 WHITE   |
| 7       | 7 ORANGE  |
| 8       | 8 WHITE   |
| 9       | 9 YELLOW  |
| 10      | 10 WHITE  |
| 11      | 11 BLACK  |
| 12      | 12 GREY   |
| 13      | 13 BROWN  |
| 14      | 14 GREY   |
| 15      | 15 RED    |
| 16      | 16 GREY   |
| 17      | 17 ORANGE |
| 18      | 18 GREY   |
| 19      | 19 YELLOW |
| 20      | 20 GREY   |
| 21      | 21 BLACK  |
| 22      | 22 BLUE   |
| 23      | 23 BROWN  |
| 24      | 24 BLUE   |
| 25      | C1 RED    |
| 26      | C2 BLUE   |
| 27      | C3 ORANGE |
| 28      | C4 BLUE   |
| 30      | C5 YELLOW |
| 31      | C5 BLUE   |

**NOTES:**

- TESTING: ALL PRODUCTS MUST BE 100% TESTED AT:  
 COND.: 5 OHM  
 INS.: 10M OHM  
 HI-V.: DC 300V 0.01 SEC
- PACKING: EACH CABLE IN A CLEAR ZIP-LOCK POLYBAG.

**MORETHANALL**  
 PCB CONNECTORS  
 Cable ASSEMBLIES  
 煜倫股份有限公司  
 www.morethanall.com

**RoHS Compliant**

|                   |             |
|-------------------|-------------|
| DRAWING BY CY     |             |
| CHECKED BY GENIUS |             |
| UNIT / mm         | SCALE 1 : 1 |
| DATE              |             |
| SIZE A4           | PPOJECTION  |

|                |
|----------------|
| TOLERANCES ARE |
| X, ±           |
| .X ±           |
| .XX ±          |
| .XXX ±         |
| ANG ±          |

照片框

**ORDER INFORMATION**

|                       |  |              |              |
|-----------------------|--|--------------|--------------|
| DF9DVI-312930-M48C-LF |  |              |              |
| SERIES                |  |              | LEADFREE     |
|                       |  | 480mm        | MALE TO MALE |
|                       |  | 30 AWG       |              |
|                       |  | 31 TO 29 WAY |              |

DESCRIPTION: