




With Insulator Support



Cover



Strain Relief



Product Specification

Material

Insulator : Glass-Filled Thermoplastic PBT, UL94V-0
 Contact : Brass
 Shell : Steel, 100u" Tin Over 50u" min Copper
 Clinch Nut : Brass, Nickel Plated
 Screwlock : Brass, Nickel Plated

Electrical

Contact Resistance : 20 milliohms
 Max at 1 AMP DC.
 Insulation Resistance : 1000
 megohms at 500 VDC
 Dielectric Withstanding Voltage :
 1000 VAC/rms 60Hz for 1 minute
 Current Rating : 3 AMP
 Volatge Rating : 250 VAC/rms 60Hz

Dimensions

| Positions | A | B | C | D | E | F |
|-----------|-------|-------|-------|-------|-------|-------|
| 9 | 30.81 | 24.99 | 16.92 | 16.33 | 11.08 | 10.16 |
| 15 | 39.20 | 33.30 | 25.25 | 24.66 | 19.39 | 17.78 |
| 25 | 53.05 | 47.04 | 38.96 | 38.38 | 33.24 | 30.48 |
| 37 | 69.40 | 63.50 | 55.42 | 54.84 | 49.86 | 45.72 |

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PJECTION

X. ± 0.38
 .X ± 0.25
 .XX ± 0.13
 .XXX ±
 ANG ±

照片框

ORDER INFORMATION

DFM-x-xx-LF
 SERIES | T LEADFREE
 09-37 WAY
 P: MALE
 S: FEMALE

DESCRIPTION: