



SPECIFICATION:
 CURRENT RATING:3 AMP
 INSULATOR RESISTANCE:1000 MΩ MIN. (AT 500V DC)
 DIELECTRIC WITHSTANDING VOLTAGE:AC 500V MIN. (FOR 1 MINUTE)
 CONTACT RESISTANCE: 15 mΩ MAX.
 WIRE SIZE: AWG26 & 28STABDED. 1. 27mm
 INSULATOOR MATERIALS: PBT+30%GLASS FIBER(UL 94V-0)
 CONTACT MATERIAL:BRASS
 FIINISHIG:GOLD OVER NICKEL:
 OPERATING TEMPRATUR:-55°~105°C.

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X. ±
 .X ±
 .XX ±
 .XXX ±
 ANG ±

PPOJECTION

照片框

ORDER INFORMATION

DFML-PN-09-LF
 SERIES | T LEADFREE
 | 09 WAY
 | NUT
 | MALE

DESCRIPTION: D-SUB IDC 9公 鉤4#40 UNC