



Specifications

Contact Resistance :  $\leq 30m$  max. at DC 100mA  
 Insulator Resistance :  $1000M$  min. at DC 500V  
 Current Rating: 1 AMP  
 Dielectric Withstanding  
 Voltage: AC 500V For 1 minute  
 Operating Temperature :  $-55^{\circ}\sim+105^{\circ}c$   
 Contact : MALE Brass  
 FEMALE Phosphor Bronze  
 Housing : PBT & 30% Glass Fiber (UL 94V-0)

Dimension

Positon	A	B	C	D
9	16.92	24.99	31.16	10.16
15	25.50	33.32	39.42	17.78
*25	38.96	47.04	53.34	30.48
37	55.45	63.50	69.68	45.72

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
 PCB CONNECTORS  
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PJECTION

X.  $\pm$   
 .X  $\pm$   
 .XX  $\pm$   
 .XXX  $\pm$   
 ANG  $\pm$

照片框

ORDER INFORMATION

DFMS-PN-xx-LF  
 SERIES | LEADFREE  
 | 09-37WAY  
 NUT  
 MALE

DESCRIPTION: SUB I.D.C TYPE