



Notes:

*Material

Body: Nylon66, UL 94V-2 Rated.
 Contact: Brass
 Plating: Au Plating on contact area
 Sn(100u"Min) plating on solder Tail.
 Nickel(50u"Min) contact underplating overall.
 Harpoon: Brass
 Plating: Overall, Ni(50u"Min).

*Mechanical

Retention Force-Terminal: 300 g Min. Per
 Insertion Force: 35 lb. Max.
 Unmating Force: 14 g Min. Per Pin Pair

*Electrical Specification

Contact Resistance: 30 mΩ Max. Initial
 Insulation Resistance: 1000 MΩ Min.,AT 500V DC
 Withstand Voltage: 500V AC,

*Environmental

Operating Temperature: -55°C TO +105°C

RoHS Compliant

TOLERANCES ARE



煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X. ±
 .X ± 0.35
 .XX ± 0.25
 .XXX ± 0.15
 ANG ± 3°

照片框

ORDER INFORMATION

DIM1-DZXL-240V15-LF

SERIES | LEADFREE
 | 1.5V
 | 240 WAY
 | NON LOCK
 | CLIP
 | DIP 180°

DESCRIPTION: DDR3-240P Shield Metal Posts Type