



**MATERIALS**

1. HOUSING : L.C.P, (UL 94V-0), BLACK
2. DUST COVER : L.C.P, (UL 94V-0), BLACK
3. TERMINAL : BRASS,  
GOLD PLATING ON CONTACT AREA,  
TIN PLATING ON SOLDER TAIL,  
UNDER NICKEL PLATING OVER ALL.
- △ 4. SHELL : STAINLESS STEEL, NICKEL PLATED.

**SPECIFICATION**

1. CURRENT RATING : 0.5 A MAX.
2. RATING VOLTAGE : 40V AC
3. DIELECTRIC WITHSTANDING VOLTAGE :  
500V AC R.M.S. FOR ONE MINUTE.
4. INSULATION RESISTANCE : 100M OHMS MIN.
5. CONTACT RESISTANCE : 30m OHMS MAX.
6. OPERATING TEMPERATURE : -55°C TO +85°C.
7. INSERTION FORCE : 4.5kgf MAX.
8. EXTRACTION FORCE : 1.0kgf MIN.



煜倫股份有限公司

www.morethanall.com

**RoHS Compliant**

DRAWING BY CY  
 CHECKED BY GENIUS  
 UNIT / mm SCALE 1 : 1  
 DATE  
 SIZE A4 PPROJECTION

TOLERANCES ARE

X. ±  
 .X ± 0.25  
 .XX ± 0.20  
 .XXX ±  
 ANG ± 3°

照片框

**ORDER INFORMATION**

DISP-SDZ3C-20-LF  
 SERIES | | | | LEADFREE  
 | | | | 20 WAY  
 | | | | CAP  
 | | | | CLIP  
 | | | | DIP 180°  
 | | | | FEMALE

DESCRIPTION: DisplayPort CONNECTOR A TYPE, DIP, VERTICAL TYPE