



PCB LAYOUT
(TOP VIEW)

未指定尺寸公差為±0.2mm

SPECIFICATIONS:

- CONTACT RESISTANCE : 20m OHM MAX.
- INSULATION RESISTANCE : 100M OHM MIN. AT 500V D.C.
- VOLTAGE WITHSTANDING : AC 500V 1 MINUTE.
- INSERTION FORCE : 5.0 KG MAX.
- WITHDRAWAL FORCE : 0.6 - 3.0 KG.
- LIFE TEST : 5,000 CYCLES MIN. AFTER TESTING , CONTACT RESISTANCE SHALL NOT EXCEED 100m OHM.
- CURRENT RATING : AC : 100V 2A
DC : 24V 1A.

4.	CONTACT TERMINAL	4	BSR-0.5H 0.7t	TIN	
3.	PLATE	1	BAKELITE	PL-PEM 1.2 t	
2.	SHIELDED TERMINAL	1	PBSR-H 0.2 t	NICKEL PLATED	
1.	BODY	1	P.B.T.		UL94V-0
P/N	PART NAME	Q'TY	MATERIAL	PLATING	REMARKS
	VERSION	APPROVAL BY	CHECKED BY	DRAWN BY	UNITS

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±
.X ±
.XX ±
.XXX ±
ANG ±

P PROJECTION

照片框

ORDER INFORMATION

DJ-M5-04-LF
SERIES | LEADFREE
4P
5.0mm
METAL

DESCRIPTION: