



T:1.6 Dimensions of PC board holes
Tolerance:±0.05(Printed-top view)

UNLESS OTHERWISE SPECIFIED, TOLERANCE ON DECIMAL: ±0.3

SPECIFICATIONS:
CONTACT RESISTANCE: 30mΩ MAX.
INSULATION RESISTANCE: 50MΩ MIN.
VOLTAGE WITHSTANDING: AC250V/1 min.
INSERTION FORCE: 6.5Kgf MAX
WITHDRAWAL FORCE: 0.5~5Kgf
LIFE TEST: 1000CYCLES
CURRENT RATING: DC 24V 1A

4	TERMINAL	8	C2680 t=0.7	Ag PLATED
3	COVER	1	PBT 4815	UL-94V0(BLACK)
2	EARTH TERMINAL	1	C2680 t=0.2	Ag PLATED
1	HOUSING	1	PBT 4815	UL-94V0(BLACK)
LTR	PART NAME	QTY	MATERIAL	REMARK

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT/mm SCALE 1:1

DATE

SIZE A4

X.±
.X±
.XX±
.XXX±
ANG±

PJECTION

照片框

ORDER INFORMATION

DJ-M5-08-LF
SERIES | LEADFREE
8P
5.0mm
METAL

DESCRIPTION: S JACK