



SPECIFICATIONS:

- 1.CONTACT RESISTANCE:20 MILLOHMS MAX.
- 2.INSERTION RESISTANCE:300M OHM AT 500V D.C
- 3.DIELECTRIC STRENGTH:1,000V AC FOR ONE MINUTE
- 4.INSULATION FOREC: 4KG MAX.
- 5.WITHDRAWAL FOREC: 1~3.5KG.

5	RIVET	1	AL	NICKEL PLATED	N/A
4	CONTACT TERMINAL	3	BRASS 0.7T	TIN PLATED	N/A
3	EARTH TERMINAL	1	PBSR-H 0.25T	TIN PLATED	N/A
2	HOUSING	1	P.B.T	BLACK	UL94V-0
1	SOCKET CASE	1	SPCC-SD 0.4T	NICKEL PLATED	N/A
P/N	PART NAME	Q'TY	MATERIAL	PLATING&COLOR	REMARKS

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X. ± 0.50

.X ± 0.30

.XX ± 0.20

.XXX ±

ANG ±

P PROJECTION

照片框

ORDER INFORMATION

DJ-P-03-LF
SERIES | LEADFREE
| 03WAY
PANEL

DESCRIPTION: