



**MATERIALS:**

1. SOCKET CASE: SPCC-SD 0.4t NICKEL PLATED
2. INSULATOR: P.B.T
3. EARTH TERMINAL: PBR-H 0.25t TIN PLATED
4. CONTACT PIN: BRAS 0.7t TIN PLATED
5. RIVET: AL NICKEL PLATED

**SPECIFICATIONS:**

1. RATING: 100V AC AT 1A or 12V DC 2A MAX
2. INSULATION RESISTANCE: 300M OHM MIN. AT 500V DC
3. DIELECTRIC STRENGTH: 250V AC FOR ONE MINUTE
4. VOLTAGE WITHSTANDING: AC 1000V FOR ONE MIN.
5. INSERTION FORCE: 6.5KG MAX.
6. WITHDRAWAL FORCE: 1-5.0KG.
7. CONTACT RESISTANCE: 20m OHM MAX.
8. OPERATION TEMPERATURE: 5 ~70
9. LIFE CYCLE: 5000~10000TIMES

**RoHS Compliant**

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1:1

DATE

SIZE A4

P PROJECTION

X. ±  
.X ±  
.XX ±  
.XXX ±  
ANG ±

照片框

**ORDER INFORMATION**

DJ-P-04-LF  
SERIES | LEADFREE  
| 04WAY  
PANEL

DESCRIPTION: DIN SOCKET