

PCB LAYOYT
(TOP VIEW)

SPECIFICATIONS:

1. CONTACT RESISTANCE : 20m OHM MAX.
2. INSULATION RESISTANCE : DC 500V 100M OHM MIN.
3. VOLTAGE WITHSTANDING : AC 500V 1 MINUTE.
4. INSERTION FORCE : 4KG MAX.
5. WITHDRAWAL FORCE : 1- 3.5KG.
6. LIFE TEST : 5,000 CYCLES MIN. AFTER TEST , CONTACT RESISTANCE SHALL NOT EXCEED 50m OHM.
7. RATING : AC 100V 1A
DC 24V 2A.

| | | | | | |
|-----|------------------|------|----------------|---------------|---------|
| 4. | CONTACT TERMINAL | 5 | BSR-0.5H 0.7 t | TIN | |
| 3. | PLATE | 1 | BAKELITE | PL-PEM | |
| 2. | EARTH TERMINAL | 1 | PBR 0.25 t | NICKEL PLATED | |
| 1. | BODY | 1 | P.B.T | | UL94V-0 |
| P/N | PART NAME | Q'TY | MATERIAL | PLATING | REMARKS |

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS


UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±
.X ±
.XX ±
.XXX ±
ANG ±

PJECTION



ORDER INFORMATION

DJ-S-05-LF
SERIES | LEADFREE
05 WAY
ALL PLASTIC

DESCRIPTION: