

**SPECIFICATIONS:**

1. CURRENT RATING : AC: 100V 1A  
DC: 12V 2A
2. CONTACT RESISTANCE : 100m OHM MAX. (AFTER 1,000 CYCLES INSERTION / EXTRACTION )
3. DIELECTRIC WITHSTANDING VOLTAGE : 500V AC FOR 1 MINUTE.
4. INSULATION RESISTANCE : 100M OHM MIN. AT 500V DC APPLIED FOR 1 MINUTE.
5. INSERTION FORCE : 3KG MAX.
6. EXTRACTION FORCE : 0.5 - 2KG.

4.	CONTACT TERMINAL	13	PBSR-H 0.2t	SILVER PLATED	
3.	EARTH TERMINAL	1	PBSR-H 0.25t	TIN	
2.	COVER	1	P.B.T.		UL94V-0
1.	BODY	1	P.B.T.		UL94V-0
P/N	PART NAME	Q'TY	MATERIAL	PLATING	REMARKS

**RoHS Compliant**

TOLERANCES ARE




**煜倫股份有限公司**

www.morethanall.com

DRAWING BY CY		X. ± .X ± .XX ± .XXX ± ANG ±
CHECKED BY GENIUS		
UNIT / mm	SCALE 1 : 1	
DATE		
SIZE A4	P PROJECTION	



**ORDER INFORMATION**



DESCRIPTION: