



PCB LAYOUT
(TOP VIEW)

SPECIFICATIONS:

1. CONTACT RESISTANCE : 20m OHM MAX.
2. INSULATION RESISTANCE : DC 500V 100M OHM MIN.
3. VOLTAGE WITHSTANDING : AC 500V 1 MINUTE.
4. INSERTION FORCE : 4KG MAX.
5. WITHDRAWAL FORCE : 1- 3.5KG.
6. LIFE TEST : 5,000 CYCLES MIN. AFTER TEST , CONTACT RESISTANCE SHALL NOT EXCEED 50m OHM.
7. RATING : AC 100V 1A
DC 24V 2A.

4.	CONTACT TERMINAL	5	BSR-0.5H 0.7 t	TIN	
3.	PLATE	1	BAKELITE	PL-PEM	
2.	EARTH TERMINAL	1	PBR 0.25 t	NICKEL PLATED	
1.	BODY	1	PA6T		UL94V-0
P/N	PART NAME	Q'TY	MATERIAL	PLATING	REMARKS

DJ-S6T-05-LF
LEADFREE
RoHS Compliant

MORETHANALL
CONNECTORS
ASSEMBLIES

煜倫股份有限公司

PART NO. DJ-S6T-05		CHECKED BY CY	DRAWING BY
DWG NO. DJ-S6T-05			
FILE NO.		PROJECTION	
UNIT / mm	SCALE 1:1		

TOLERANCES ARE
.X ± 0.2
.XX ±
.XXX ±
AWG

DESCRIPTION:		AREA	REVISIONS	HK	DATE